

Ref: MKO/LT14-048
Date: July 30, 2014

Subject: **LEXAN™ sheet and Glow Wire**

Dear Customer,

Based on in-house measurement and experience, we can state that the Glow Wire Flammability Index (GWFI) (IEC 60695-2-12) of solid LEXAN™ solid sheet:

Standard LEXAN™ 9030, Exell D, SG305, etc. will pass 850 °C

Flame retardant: LEXAN™ F2000, F6000, etc. will pass 960 °C

I hope to have informed you satisfactorily.

Yours faithfully,

A handwritten signature in black ink, appearing to read 'M.F.M. Koppers', with a long horizontal stroke extending to the right.

Ir. M.F.M. Koppers
Agency Relations – Specialty Film & Sheet

™trademark of SABIC Innovative Plastics IP BV.

SABIC Innovative Plastics B.V.
PO Box 117, 4600 AC
Plasticslaan 1, 4612 PX
Bergen op Zoom
Netherlands
T: +31 164 291302
F: +31 164 292194
E: thijs.koppers@sabic-ip.com
www.sabic-ip.com

ANY SALE OF PRODUCTS OR DELIVERY OF CUSTOMER SUPPORT AND ADVICE BY SABIC INNOVATIVE PLASTICS HOLDING BV, ITS SUBSIDIARIES AND AFFILIATES ("SELLER"), IS MADE EXCLUSIVELY UNDER SELLER'S STANDARD CONDITIONS OF SALE which can be located at <http://www.sabic-ip.com>. **SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OF ITS PRODUCTS IN ANY CUSTOMER'S APPLICATION.** Each customer should determine the suitability of SELLERS materials for the customer's particular use through appropriate testing and analysis.