

DECLARATION OF PERFORMANCE

No. HPA 001 01-05-13

HardiePanel®

1. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Manufacturing code, CE mark and Classification to EN12467 printed on rear face – NT Category A Class 2 to EN 12467:2004.

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Fibre cement cladding panel for façades

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**James Hardie Building Products
17 Unytite Drive
Peru
Illinois
61354
USA**

**James Hardie Building Products
1000 James Hardie Way
Pulaski
Virginia
24301
USA**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**James Hardie Building Products Ltd
7, Albemarle Street
London
W1S 1HQ**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

1+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Manufactured and tested in accordance with EN12467 : 2004

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

BBA Certificate no. 05/4248

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


General Property	Unit or Characteristic	Result	Test Method
Dimensional Tolerances	Length	Pass Level 1	EN 12467
	Width		
	Thickness		
	Straightness of edges		
	Squareness of corners		
Weight	kg/m ²	11.2	
Average density	Saturated, g/cm ³	1.3	EN 12467
Water Impermeability	Physical Observations	Pass	
Water Absorption	% by mass	>36%	ASTM C1186
Moisture Movement, 30 - 90% RH	% Linear change	0.05%	
Moisture Content		4.00%	
Modulus of rupture (Mpa)	Saturated & EQ average	Pass	EN 12467
Category, class		NT Category A Class 2	
Warm Water Evaluation		Pass	
Freeze/Thaw Resistance			
Soak/dry			
Heat/Rain Resistance			
Surface Burning Characteristics	Fuel Contributed	A2	EN13501-1
	Smoke Development Index	S1	
	Flames Droplets Index	D0	
	Euroclass	A2,s1-d0	

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr M Longfellow – General Manager Europe

Amsterdam, 1/5/2013



(insert place and date of issue)

(insert signature)