

**EC - DECLARATION OF PERFORMANCE / CPR**

Nr: QS/2014/02

- 1) Identification code : CE02  
2) Type : Light transmitting profiled GRP sheet with a 0.8 mm nominal thickness and class 1 as per EN 1013:2012. All as defined in accordance with NA to EN 1013 for discontinuously laid roof, wall and ceiling linings for buildings.  
3) Intended use : Light transmitting GRP sheet for use as a rooflight or wall light.  
4) Manufacturer : Polser Şeffaf Çatı Örtüleri Sanayi ve Ticaret A.Ş.  
5) Authorized representative : Not applicable  
6) Assessment and verification of consistency of performance : System 4  
7) Notified body and tasks : Not applicable  
8) European technical assessment : Not applicable

Essential Characteristics	Declared performance	Harmonized standart
External fire performance	NPD	EN 1013:2012
Reaction to fire	NPD	
Release of dangerous substances	NPD	
Dimensional tolerances	Pass	
Soft body impact resistance	NPD	
Mechanical resistance	NPD	
Resistance to fixings	See manufacturer's fixing instructions	
Durability to ageing		
- yellowness index	NPD	
- of the light transmission	NPD	
- flexural strength for	NPD	
*flexural strength	NPD	
*flexural modulus	NPD	

9) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration is issued under the sole responsibility of the manufacture identified in point 4.

Signed for and on behalf of the manufacturer by:

Sevgin Aydın

Quality Assurance Chief

Polser A.Ş. ....

