



## QMFZ2.E100599 Plastics - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).  
Click on a product designation for complete information.

[Page Bottom](#)

### Plastics - Component

[See General Information for Plastics - Component](#)

**PROFINE GMBH - KOMMERLING KUNSTSTOFFE**  
ZWEIBRUCKER STR 200  
66954 PIRMASENS, GERMANY

E100599

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
<b>Polyvinylchloride (PVC), PVC structural foam, furnished as sheets.</b>											
<b>Koemacel 654/10</b>	WT	10.0	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Koemacel 654/4-6</b>	WT	4.0-6.0	V-0	-	-	50	50	50	-	-	-
<b>Komaprint A (i)</b>	WT	2.0 - 4.0	V-0, 5VA	-	-	50	50	50	-	-	-
		6.0 - 6.6	V-0, 5VA	-	-	50	50	50			
<b>Komaprint B (k)</b>	WT	5.0 - 5.5	V-0, 5VA	-	-	50	50	50	-	-	-
<b>Komaprint C (l)</b>	WT	8.0 - 10.0	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komatex 1-6</b>	WT	1.0	V-0, 5VB	-	-	50	50	50	-	-	-
	ALL	2.0	V-0, 5VB	-	-	50	50	50			
		3.0	V-0, 5VA	-	-	50	50	50			
		6.0	V-0, 5VA	-	-	50	50	50			
<b>Komatex New (c)</b> [density range: 502-614 kg/m <sup>3</sup> ]	ALL	3	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komatex New A (d)</b>	WT	1.0 - 1.1	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komatex New B (e)</b>	WT	2.0 - 4.0	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komatex New C (f)</b>	WT	5.0 - 5.5	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komatex New D (g)</b>	WT	6.0 - 6.6	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komatex New E (h)</b>	WT	8.0 - 10.0	V-0, 5VA	-	-	50	50	50	-	-	-
<b>Komatex/1-3</b>	WT	1.0-3.0	V-0	-	-	50	50	50	-	-	-

<b>Komatex/3-6</b>	WT	1.0-3.0	V-0	-	-	50	50	50	-	-	-
	ALL	3.0-6.0	V-0	-	-	50	50	50			
<b>Polyvinylchloride (PVC), structural foam w/ smooth outer skin, furnished as sheets.</b>											
<b>Koemacel 652</b>	WT	9.5	V-0	-	-	50	50	50	-	-	-
<b>Polyvinylchloride (PVC), furnished as sheets.</b>											
<b>Komadur ES / D 1-10</b>											
	ALL	0.9	V-0, 5VB	-	-	50	50	50	-	-	-
<b>Komadur ES / D 669</b>	WT	0.97	V-0	-	-	50	50	50	-	-	-
<b>Komadur WA (a)</b>	WT, GY	1.0	V-0	-	-	50	50	50	-	-	-
		6.0	V-0	-	-	50	50	50			
		12.0	V-0	-	-	50	50	50			
<b>Komadur WA 1-30 (a)</b>											
	NC, WT, GY	0.9	V-0, 5VB	-	-	50	50	50	-	-	-

- (a) - Gray color may be either light or dark gray
- (c) - Excluding color WT
- (d) - for density range of 0.734 - 0.898 g/cc
- (e) - for density range of 0.552 - 0.674 g/cc
- (f) - for density range of 0.473 - 0.578 g/cc
- (g) - for density range of 0.503 - 0.614 g/cc
- (h) - for density range of 0.437 - 0.534 g/cc
- (i) - for density range of 0.482 - 0.590 g/cc
- (k) - for density range of 0.463 - 0.565 g/cc
- (l) - for density range of 0.446 - 0.545 g/cc

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2018-03-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".